

Goneo Combi 7kW EV Charger

PV Compatible

- 0 emission PV charging
- Seamless integration with PV systems
- Adjustable current for optimized PV usage

Safe & Convenient

- 30mA Type A + 6mA DC
- Relay-sticking protection
- Ergonomic and user-friendly enclosure design

Intelligent

- Multi communications
- App charging scheduling
- Dynamic load balancing



Specification	Parameter	Combi 7kW
Electrical Specs	Power Supply	1P+N+PE
	Rated Voltage	230V
	Rated Current	32A
	Frequency	50/60Hz
	Rated Power	7KW
Basic Parameters	Product Standard	European Standard
	Connector	Type 2 Cable
	Cable Length	7m Cable
	Housing Material	PC
	Color	Panel: Ocean Blue, Base: Space Silver
	Installation	Wall/Pole Mount (Optional)
	LED Indicator	Red/Green/Yellow
	RFID Reader	MIFARE ISO/IEC 14443A
	Activation Method	Plug & Charge / RFID / APP
Communication	WiFi&Bluetooth & Ethernet	Standard
	WiFi&Bluetooth&4G	WiFi&Bluetooth
	OCPP	OCPP 1.6 (JSON)
Safety	RCD	30mA Type A+6mA DC
	IP Rating	IP65
	IK Rating	IK08
	Electrical Protection	Over/Under Voltage, Overload, Short Circuit, Leakage, Grounding, Surge, Over/Under Temperature Protection
	Certifications	CE/CB/RoHS/TR25
	Compliance Standards	IEC 61851-1:2017 EN IEC 61851-1:2019 EN IEC 61851-21-2:2021 EN IEC 61000-6-1:2019 EN IEC 61000-6-3:2007 + A1 EN 300 328 V2.2.2:2019 EN 300 330 V2.1.1:2017 EN 301 489-1 V2.2.3:2019 EN 301 489-3 V2.1.1:2019 EN 301 489-17 V3.2.0:2017 EN 62311:2020 BS 7671:2018+A2:2022
	Warranty	2 Years
Operating Environment	Operating Temperature	-30 C ~+50 C
	Operating Humidity	5%-95%
	Operating Altitude	≤2000m
Packaging	Product Dimensions	344*192*100mm (H*W*D)
	Package Dimensions	430*330*235mm (L*W*H) 4M Cable
	Net Weight	4kg
	Gross Weight	5kg
	Outer Packaging	Carton Box



Goneo Combi Pro 22kW EV Charger

Versatile

- Customizable enclosure choice
- Activated by RFID
- Convenient back plate for easy cable access

Intelligent

- Multi communications
- App charging scheduling
- Dynamic load balancing

PV Compatible

- 0 emission PV charging
- Seamless integration with PV systems
- Adjustable current for optimized PV usage

Safe & Convenient

- 30mA Type A + 6mA DC
- Relay-sticking protection
- Ergonomic and user-friendly enclosure design



Specification	Parameter	Combi Pro 22kW
Electrical Specs	Power Supply	3P+N+PE
	Rated Voltage	400V AC
	Rated Current	32A
	Frequency	50/60Hz
	Rated Power	22KW
Basic Parameters	Product Standard	European Standard
	Connector	Type 2 Cable
	Cable Length	7m
	Housing Material	PC
	Color	Panel: Blue Grey, Base: Black
	Installation	Wall/Pole Mount (Optional)
	LED Indicator	Red/Green/Yellow
	RFID Reader	MIFARE ISO/IEC 14443A
Communication	Activation Method	Plug & Charge / RFID / APP
	WIFI&Bluetooth & Ethernet	Standard (Implementation: Non-surface-mounted 4G module)
	WIFI&Bluetooth&4G	WIFI&Bluetooth
Safety	OCPP	OCPP 1.6 (JSON)
	RCD	30mA Type A+6mA DC
	IP Rating	IP65
	IK Rating	IK10
	Electrical Protection	Over/Under Voltage, Overload, Short Circuit, Leakage, Grounding, Surge, Over/Under Temperature Protection
	Certifications	CE/CB/RoHS/Reach/TR25
	Compliance Standards	IEC 61851-1:2017 EN IEC 61851-1:2019 EN IEC 61851-21-2:2021 EN IEC 61000-6-1:2019 EN IEC 61000-6-3:2007 + A1 EN 300 328 V2.2.2:2019 EN 300 330 V2.1.1:2017 EN 301 489-1 V2.2.3:2019 EN 301 489-3 V2.1.1:2019 EN 301 489-17 V3.2.0:2017 EN 62311:2020 BS 7671:2018+A2:2022*
	Warranty	2 Years
	Operating Temperature	-30 °C ~+50 °C
	Operating Humidity	5%-95%
Operating Environment	Operating Altitude	≤2000m
Packaging	Product Dimensions	374x226x164 mm (H*W*D)
	Package Dimensions	430*330*235 mm (L*W*H)
	Net Weight	3.5kg
	Gross Weight	7.0kg
	Outer Packaging	Carton Box